

250W

MHD Flexi Solar Panel

– top exit

Part code: STPVFU250



The 250w MHD Flexi solar panel combines shingled monocrystalline solar cells to deliver super efficient power generation with a tough ETFE top sheet for longevity and robust impact resistance.

At just 2mm thick, this ultra-lightweight panel is ideal for flat roofs as well as surfaces with a slight curve making it the perfect choice for camper vans and boat decks.

To ensure long term performance in the most extreme environments, the panels are tested to ASTM B117 - ISO9227 for saltwater spray over 1000 hours as well as accelerated Ultraviolet (UV) testing to ISO 4892.

The 250w solar panel comes with 2 x 0.9m connection cables fitted with MC4 connectors and 2 x 3m cable with MC4 connectors so the panels can be easily joined together to create a solar array. The panel is supplied with a 4-year module warranty.

A charge controller should be used with this panel to protect the battery from being overcharged and to prevent reverse of current drain.

For optimum battery performance, pair your panel with a **Lifos Go advanced lithium battery**. Connect up to four Lifos batteries in parallel or series to increase the current or voltage.

For further information from our Technical Team, please contact support@solartechnology.co.uk




SPECIFICATIONS


Size	1475x890x2mm
Weight (Kg)	4.5
*Watts per day (W)	1500
*Amp hours per day (A)	61.50
Charge controller	20Ah
Vmp (VDC) nominal voltage	24.4V
Imp (A) nominal current	10.25A
Voc (V)	28.8V
Isc (A) short circuit current	10.86A

**Watts and Amp hours/day based on six hours of average daily peak sunshine hours.*

STPVFU250



4*41 250W 23.4V 890*1475*2mm



Solar
Technology
International

Unit 6, Station Drive, Bredon, Gloucestershire GL20 7HH
T 01684 774 000 F 01684 773 000
sales@solartechnology.co.uk www.solartechnology.co.uk